

# ZEDOS SR™ - CEILING SURFACE

Project Name:	Fixture Type:
Fixture Code:	Quantities:



# ZEDOS SR™ - CEILING SURFACE

## GENERAL SPECIFICATION

**Body and trim**

Steel and aluminum.

**Diffusers**

Opal polycarbonate.

**Luminaire orientation**

Ceiling or wall.

**Delivered Lumens**

Delivered lumens & LPW based on 3000K (min 80 CRI).

**Finish**

Powder coated or plated as listed.

**Drivers**

HPF electronic, 120-277V (EU-240V). 0-10V, 1% dimming standard.


**Mechanical**

Mounts directly to a junction box (by others - North America only).

**Approvals**

Damp Location (Indoor use only).

## OPTICS & FEATURES



# ZEDOS SR™ - CEILING SURFACE

## HOW TO ORDER

### A. LUMINAIRE

**681660** 15.7", 28W, 2056 lms      **682160** 20.8", 28W, 2167 lms      **682163** 20.8", 36W, 2856 lms

### B. CCT

**30** 3000K (min 80 CRI)      **35** 3500K (min 80 CRI)      **40** 4000K (min 80 CRI)

### C. FINISH

**WH** White      **MS** Silver Metallic      **SN** Satin Nickel      **OT** Other painted finish (RAL number required)

**F40** Other Non-RAL painted finish (sample chip required)

OT & BL1 have a one time set-up charge regardless of quantity.

## TECHNICAL DATA

### LUMINAIRE

Code	681660	682160	682163
Power (LED)	28W	28W	36W
Delivered lms	2056	2167	2856
LPW	73	77	80
Diameter (A)	15.7"	20.8"	20.8"
Depth (D)	4"	4"	4"
Weight	4lb	5.5lb	5.5lb

## APPROVALS



# ZEDOS SR™ - CEILING SURFACE

## DIMENSIONAL DIAGRAMS

