

ZEDOS TSR™ - SUSPENDED

Project Name:

Fixture Type:

Fixture Code:

Quantities:



ZEDOS TSR™ - SUSPENDED

GENERAL SPECIFICATION

Body and trim

Steel and aluminium.

Finish

Gear tray, powder coated gloss white. Trim, powder coated or plated as listed.

Dust covers

Clear polycarbonate.

Remote Emergency

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility.

The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (NA only) Maximum distance between wall/ceiling plate and luminaire is 4.5m/15'. Test switch fits a single gang box (not supplied).

Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

Suspension

Single tube with four decorative tubes.

Lens

Acrylic.

Drivers

HPF electronic, 120/277V (EU-240V), 0-10V, 1% dimming standard.

L70 @25°C (77°F)

> 50,000 hrs.

OPTICS & FEATURES



Suspended Direct/Indirect

ZEDOS TSR™ - SUSPENDED

HOW TO ORDER

A. LUMINAIRE

687310 687310

687320 687320

687330 687330

B. CCT

30 3000K (min 80 CRI)

35 3500K (min 80 CRI)

40 4000K (min 80 CRI)

C. FINISH

WH White

MB Metallic Bronze

MS Silver Metallic

PC Polished Chrome

SB Satin Brass

SC Satin Chrome

SN Satin Nickel

OT Other painted finish (RAL number required)

F40 Other Non-RAL painted finish (sample chip required)

OT & BL1 have a one time set-up charge regardless of quantity.

D. LENS

OP Opal

E. SPECIFY OPTIONS

RE Remote Emergency (max distance 10 ft, 120/277V)

CB Cradle Bars

SW Swivel Canopy (42 degrees)

F. DIMMING

DA DALI Drivers

DX DMX Drivers

G. SUSPENSION LENGTH

S1 6" Additional Suspension Length

S2 12" Additional Suspension Length

S3 18" Additional Suspension Length

S4 24" Additional Suspension Length

ZEDOS TSR™ - SUSPENDED

TECHNICAL DATA

LUMINAIRE

Code	687310	687320	687330
Power (LED)	150W	211W	282W
Delivered lms	15439	22631	30043
LPW	103	107	107
Diameter (A)	29"	37"	47"
Diameter (B)	5.7"	5.7"	7.9"
Depth (D)	6.5"	7"	9"
Height (H)	24"	24"	29.5"
Height (A)	1"	1"	1.75"

APPROVALS



IP20

ZEDOS TSR™ - SUSPENDED

DIMENSIONAL DIAGRAMS

