| Project Name: | Fixture Type: |
|---------------|---------------|
| | |
| | |
| Fixture Code: | Quantities: |



GENERAL SPECIFICATION

Body and trim

Steel and aluminium.

Finish

Gear tray, powder coated gloss white. Trim, powder coated or plated as listed.

Dust covers

Clear polycarbonate.

Remote Emergency

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (NA only) Maximum distance between wall/ceiling plate and luminaire is 4.5m/15′. Test switch fits a single gang box (not supplied).

Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

OPTICS & FEATURES



Suspended Direct/Indirect

Suspension

Single tube with four decorative tubes.

Diffusers

Acrylic.

Drivers

HPF electronic, 120/277V (EU-240V), 0-10V, 1% dimming standard.

L70 @25°C (77°F)

> 50,000 hrs.

HOW TO ORDER

A. LUMINAIRE

687310 687310 **687320** 687320 **687330** 687330

B. CCT

30 3000K (min 80 CRI) **35** 3500K (min 80 CRI) **40** 4000K (min 80 CRI)

C. FINISH

WH White MB Metallic Bronze MS Silver Metallic PC Polished Chrome

SB Satin BrassSC Satin ChromeSN Satin NickelOT Other painted finish (RAL number

required)

F40 Other Non-RAL painted finish (sample chip required)

OT & BL1 have a one time set-up charge regardless of quantity.

D. DIFFUSER

OP Opal

E. SPEICFY OPTIONS

RE Remote Emergency (max distance **CB** Cradle Bars **SW** Swivel Canopy (42 degrees)

10 ft, 120/277V)

F. DIMMING

DA DALI Drivers **DX** DMX Drivers

G. SUSPENSION LENGTH

S1 6" Additional Suspension Length **S2** 12" Additional Suspension Length **S3** 18" Additional Suspension Length **S4** 24" Additional Suspension Length

TECHNICAL DATA

LUMINAIRE

| Code | 687310 | 687320 | 687330 |
|---------------|--------|--------|--------|
| Power (LED) | 150W | 211W | 282W |
| Delivered Ims | 15439 | 22631 | 30043 |
| LPW | 103 | 107 | 107 |
| Diameter (A) | 29" | 37" | 47" |
| Diameter (B) | 5.7" | 5.7" | 7.9" |
| Depth (D) | 6.5" | 7" | 9" |
| Height (H) | 24" | 24" | 29.5" |
| Height (A) | 1" | 1" | 1.75" |

APPROVALS











DIMENSIONAL DIAGRAMS

