

# ZEDOS TSR™ - SUSPENDED

Project Name:

Fixture Type:

Fixture Code:

Quantities:



# ZEDOS TSR™ - SUSPENDED

## GENERAL SPECIFICATION

### Body and trim

Steel and aluminium.

### Finish

Gear tray, powder coated gloss white. Trim, powder coated or plated as listed.

### Dust covers

Clear polycarbonate.

### Remote Emergency

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (NA only) Maximum distance between wall/ceiling plate and luminaire is 4.5m/15'. Test switch fits a single gang box (not supplied).

### Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

### Suspension

Single tube with four decorative tubes.

### Lens

Acrylic.


### Drivers

HPF electronic, 120/277V (EU-240V), 0-10V, 1% dimming standard.

### L70 @25°C (77°F)

> 50,000 hrs.

## OPTICS & FEATURES



Suspended Direct/Indirect

# ZEDOS TSR™ - SUSPENDED

## HOW TO ORDER

### A. LUMINAIRE

**687310** 687310

**687320** 687320

**687330** 687330

### B. CCT

**30** 3000K (min 80 CRI)

**35** 3500K (min 80 CRI)

**40** 4000K (min 80 CRI)

### C. FINISH

**WH** White

**MB** Metallic Bronze

**MS** Silver Metallic

**PC** Polished Chrome

**SB** Satin Brass

**SC** Satin Chrome

**SN** Satin Nickel

**OT** Other painted finish (RAL number required)

**F40** Other Non-RAL painted finish  
(sample chip required)

---

OT & BL1 have a one time set-up charge regardless of quantity.

### D. LENS

**OP** Opal

### E. SPECIFY OPTIONS

**RE** Remote Emergency (max distance  
10 ft, 120/277V)

**CB** Cradle Bars

**SW** Swivel Canopy (42 degrees)

### F. DIMMING

**DA** DALI Drivers

**DX** DMX Drivers

### G. SUSPENSION LENGTH

**S1** 6" Additional Suspension Length

**S2** 12" Additional Suspension Length

**S3** 18" Additional Suspension Length

**S4** 24" Additional Suspension Length

# ZEDOS TSR™ - SUSPENDED

## TECHNICAL DATA

### LUMINAIRE

Code	687310	687320	687330
Power (LED)	150W	211W	282W
Delivered lms	15439	22631	30043
LPW	103	107	107
Diameter (A)	29"	37"	47"
Diameter (B)	5.7"	5.7"	7.9"
Depth (D)	6.5"	7"	9"
Height (H)	24"	24"	29.5"
Height (A)	1"	1"	1.75"

---

## APPROVALS



IP20



# ZEDOS TSR™ - SUSPENDED

## DIMENSIONAL DIAGRAMS

