Fixture Code:	Quantities:



#### **GENERAL SPECIFICATION**

Body and trim

Steel and aluminum.

Lens

Opal polycarbonate.

Luminaire orientation

Ceiling or wall.

**Delivered Lumens** 

Delivered lumens & LPW based on 3000K (min 80 CRI).

Finish

Powder coated or plated as listed.

**Drivers** 

HPF electronic, 120-277V (EU-240V). 0-10V, 1% dimming standard.

Mechanical

Mounts directly to a junction box (by others - North America only).

Approvals

Damp Location (Indoor use only).

#### **OPTICS & FEATURES**





ng Direct

#### **HOW TO ORDER**

#### A. LUMINAIRE

**681670** 15.7", 28W, 1793 lms **682170** 20.8", 28W, 1949 lms **682173** 20.8", 36W, 2568 lms

B. CCT

**30** 3000K (min 80 CRI) **35** 3500K (min 80 CRI) **40** 4000K (min 80 CRI)

C. FINISH

**WH** White **MS** Silver Metallic **SN** Satin Nickel **F39** Other painted finish (RAL number

required)

**F40** Other Non-RAL painted finish (sample chip required)

F39 & F40 have a one time set-up charge regardless of quantity.

#### **TECHNICAL DATA**

#### **LUMINAIRE**

Code	681670	682170	682173
Power (LED)	28W	28W	36W
Delivered Ims	1793	1949	2568
LPW	64	70	72
Diameter (A)	15.7"	20.8"	20.8"
Depth (D)	4"	4"	4"
Weight	4lb	5.5lb	5.5lb

#### **APPROVALS**













### **DIMENSIONAL DIAGRAMS**

