Fixture Code:	Quantities:
Project Name:	Fixture Type:



### **GENERAL SPECIFICATION**

#### Body and trim

Steel and aluminium.

#### Finish

Gear tray, powder coated gloss white. Trim, powder coated or plated as listed.

#### **Dust covers**

Clear polycarbonate.

### **Remote Emergency**

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (NA only) Maximum distance between wall/ceiling plate and luminaire is 4.5m/15′. Test switch fits a single gang box (not supplied).

### **Delivered Lumens**

Delivered lumens & LPW based on 3000K (min 80 CRI).

### **OPTICS & FEATURES**



Suspended Direct/Indirect

#### Suspension

Single tube with four decorative tubes.

#### **Diffusers**

Acrylic.

### Drivers

HPF electronic, 120/277V (EU-240V), 0-10V, 1% dimming standard.

### L70 @25°C (77°F)

> 50,000 hrs.

### **HOW TO ORDER**

#### A. LUMINAIRE

**687010** 687010 **687020** 687020 **687030** 687030

B. CCT

**30** 3000K (min 80 CRI) **35** 3500K (min 80 CRI) **40** 4000K (min 80 CRI)

C. FINISH

WH White MB Metallic Bronze MS Silver Metallic PC Polished Chrome

SB Satin BrassSC Satin ChromeSN Satin NickelOT Other painted finish (RAL number

required)

**F40** Other Non-RAL painted finish (sample chip required)

OT & BL1 have a one time set-up charge regardless of quantity.

### **D. DIFFUSER**

**OP** Opal

#### E. DIMMING

**DA** DALI Drivers **DX** DMX Drivers

F. OPOTIONS

RE Remote Emergency (max distance CB Cradle Bars SW Swivel Canopy (42 degrees)

10 ft., 120/277V)

### **G. SUSPENSION LENGTHS**

**S1** 6" Additional Suspension Length **S2** 12" Additional Suspension Length **S3** 18" Additional Suspension Length **S4** 24" Additional Suspension Length

### **TECHNICAL DATA**

### **LUMINAIRE**

Code	687010	687020	687030
Power (LED)	150W	211W	282W
Delivered Ims	15439	22631	30043
LPW	103	107	107
Diameter (A)	29"	37"	47"
Diameter (B)	5.7"	5.7"	7.9"
Depth (D)	6.5"	7"	9"
Height (H)	24"	24"	29.5"
Height (A)	1"	1"	1.75"

### **APPROVALS**











### **DIMENSIONAL DIAGRAMS**

