ZEDOS™ - SUSPENDED

Project Name:

Fixture Type:

Fixture Code:

Quantities:



© 2026 Beta-Calco Inc. Specifications are subject to change without notice

ZEDOS™ - SUSPENDED

GENERAL SPECIFICATION

Body and trim
Steel and aluminium.

Finish
Gear tray, powder coated gloss white. Trim, powder coated or plated as listed.

Dust covers
Clear polycarbonate.

Remote Emergency
Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (NA only) Maximum distance between wall/ceiling plate and luminaire is 4.5m/15'. Test switch fits a single gang box (not supplied).

Delivered Lumens
Delivered lumens & LPW based on 3000K (min 80 CRI).

Suspension
Single tube with four decorative tubes.

Lens
Acrylic.

Drivers
HPF electronic, 120/277V (EU-240V), 0-10V, 1% dimming standard.

L70 @25°C (77°F)
> 50,000 hrs.

OPTICS & FEATURES



Suspended Direct/Indirect

© 2026 Beta-Calco Inc. Specifications are subject to change without notice

ZEDOS™ - SUSPENDED

HOW TO ORDER

A. LUMINAIRE

687010 687010

687020 687020

687030 687030

B. CCT

30 3000K (min 80 CRI)

35 3500K (min 80 CRI)

40 4000K (min 80 CRI)

C. FINISH

WH White

MB Metallic Bronze

MS Silver Metallic

PC Polished Chrome

SB Satin Brass

SC Satin Chrome

SN Satin Nickel

OT Other painted finish (RAL number required)

F40 Other Non-RAL painted finish (sample chip required)

OT & BL1 have a one time set-up charge regardless of quantity.

D. LENS

OP Opal

E. DIMMING

DA DALI Drivers

DX DMX Drivers

F. OPOTIONS

RE Remote Emergency (max distance 10 ft., 120/277V)

CB Cradle Bars

SW Swivel Canopy (42 degrees)

G. SUSPENSION LENGTHS

S1 6" Additional Suspension Length

S2 12" Additional Suspension Length

S3 18" Additional Suspension Length

S4 24" Additional Suspension Length

© 2026 Beta-Calco Inc. Specifications are subject to change without notice

ZEDOS™ - SUSPENDED

TECHNICAL DATA

LUMINAIRE

Code	687010	687020	687030
Power (LED)	150W	211W	282W
Delivered lms	15439	22631	30043
LPW	103	107	107
Diameter (A)	29"	37"	47"
Diameter (B)	5.7"	5.7"	7.9"
Depth (D)	6.5"	7"	9"
Height (H)	24"	24"	29.5"
Height (A)	1"	1"	1.75"


APPROVALS



© 2026 Beta-Calco Inc. Specifications are subject to change without notice

ZEDOS™ - SUSPENDED

DIMENSIONAL DIAGRAMS



© 2026 Beta-Calco Inc. Specifications are subject to change without notice