

ZEDOS™ - SUSPENDED

Project Name:

Fixture Type:

Fixture Code:

Quantities:



ZEDOS™ - SUSPENDED

GENERAL SPECIFICATION

Body and trim

Steel and aluminium.

Finish

Gear tray, powder coated gloss white. Trim, powder coated or plated as listed.

Dust covers

Clear polycarbonate.

Remote Emergency

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (NA only) Maximum distance between wall/ceiling plate and luminaire is 4.5m/15'. Test switch fits a single gang box (not supplied).

Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

Suspension

Single tube with four decorative tubes.

Diffusers

Acrylic.

Drivers

HPF electronic, 120/277V (EU-240V), 0-10V, 1% dimming standard.

L70 @25°C (77°F)

> 50,000 hrs.

MOUNTING & OPTICS



Suspended Direct/Indirect

ZEDOS™ - SUSPENDED

HOW TO ORDER

A. LUMINAIRE

687010 687010

687020 687020

687030 687030

B. CCT

30 3000K (min 80 CRI)

35 3500K (min 80 CRI)

40 4000K (min 80 CRI)

C. FINISH

WH White

MB Metallic Bronze

MS Silver Metallic

PC Polished Chrome

SB Satin Brass

SC Satin Chrome

SN Satin Nickel

OT Other painted finish (RAL number required)

F40 Other Non-RAL painted finish
(sample chip required)

OT & BL1 have a one time set-up charge regardless of quantity.

D. DIFFUSER

OP Opal

E. DIMMING

DA DALI Drivers

DX DMX Drivers

F. OPOTIONS

RE Remote Emergency (max distance
10 ft., 120/277V)

CB Cradle Bars

SW Swivel Canopy (42 degrees)

G. SUSPENSION LENGTHS

S1 6" Additional Suspension Length

S2 12" Additional Suspension Length

S3 18" Additional Suspension Length

S4 24" Additional Suspension Length



ZEDOS™ - SUSPENDED

TECHNICAL DATA

LUMINAIRE

| Code | 687010 | 687020 | 687030 |
|---------------|--------|--------|--------|
| Power (LED) | 150W | 211W | 282W |
| Delivered lms | 15439 | 22631 | 30043 |
| LPW | 103 | 107 | 107 |
| Diameter (A) | 29" | 37" | 47" |
| Diameter (B) | 5.7" | 5.7" | 7.9" |
| Depth (D) | 6.5" | 7" | 9" |
| Height (H) | 24" | 24" | 29.5" |
| Height (A) | 1" | 1" | 1.75" |

APPROVALS



ZEDOS™ - SUSPENDED

DIMENSIONAL DIAGRAMS

