

# ZEDOS TSR™ - WALL OR CEILING SURFACE

Project Name:

Fixture Type:

Fixture Code:

Quantities:



# ZEDOS TSR™ - WALL OR CEILING SURFACE

## GENERAL SPECIFICATION

### Body and trim

Steel and aluminum.

### Finish

Powder coated or plated as listed.

### Diffusers

Opal polycarbonate.

### Drivers

HPF electronic, 120-277V (EU-240V). 0-10V, 1% dimming standard.

### Luminaire orientation

Ceiling or wall.

### Mechanical

Mounts directly to a junction box (by others - North America only).

### Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

### Approvals

Damp Location (Indoor use only).

## MOUNTING & OPTICS



Ceiling

# ZEDOS TSR™ - WALL OR CEILING SURFACE

## HOW TO ORDER

### A. LUMINAIRE

**681690** 68 1690

**682190** 68 2190

**682193** 68 2193

### B. CCT

**30** 3000K (min 80 CRI)

**35** 3500K (min 80 CRI)

**40** 4000K (min 80 CRI)

### C. FINISH

**WH** White

**MS** Silver Metallic

**SN** Satin Nickel

**F39** Other painted finish (RAL number required)

**F40** Other Non-RAL painted finish  
(sample chip required)

F39 & F40 have a one time set-up charge regardless of quantity.

## TECHNICAL DATA

### LUMINAIRE

Code	<b>681690</b>	<b>682190</b>	<b>682193</b>
Power (LED)	28W	28W	36W
Delivered lms	2056	2167	2856
LPW	73	77	80
Diameter (A)	15.7"	20.8"	20.8"
Depth (D)	4"	4"	4"
Weight	4lb	5.5lb	5.5lb

## APPROVALS



# ZEDOS TSR™ - WALL OR CEILING SURFACE

## DIMENSIONAL DIAGRAMS

